

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
11 March 2004 (11.03.2004)

PCT

(10) International Publication Number
WO 2004/020964 A1

- (51) International Patent Classification⁷: **G01L 5/10**
- (21) International Application Number:
PCT/NZ2003/000191
- (22) International Filing Date: 29 August 2003 (29.08.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
521094 30 August 2002 (30.08.2002) NZ
- (71) Applicant (for all designated States except US):
HOLMES SOLUTIONS LIMITED [NZ/NZ]; 61
Cambridge Terrace, Christchurch (NZ).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **BULL, Desmond,**
Kenneth [NZ/NZ]; 19, Thornwood Place, Redwood,
Christchurch (NZ). **ALLINGTON, Christopher, James**
[NZ/NZ]; 118 Roker Street, Somerfield, Christchurch
(NZ). **NEWTON, Richard, John [GB/NZ];** 3, Davie
Street, Kaiapoi (NZ).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: APPARATUS FOR TESTING TENSION OF ELONGATED FLEXIBLE MEMBER



(57) Abstract: A handheld apparatus (2) for checking the tension of the wire (15) includes a support (3) with two spaced pegs (5,6) mounted on it. A spring (7) mounted on the support (3) between the two pegs. A strain gauge (14) is mounted on the spring and measures the displacement of the spring (7). A fully portable power supply is connected to a computer (9) with a readout (8). In use, the wire (15) is arranged in a predetermined path over and/or under the pegs (5,6) so that it presses against the spring (7). The amount the spring (7) is displaced, which is related to the tension, is measured by the signal from the strain gauge. The signal is passed to the computer (9), which calculates the tension from this measurement and displays the result on the readout (8).

WO 2004/020964 A1